

证明

CERTIFICATE

本证明之附件是向中国专利局作为受理局提交的下列国际申请副本
THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY OF THE BELOW IDENTIFIED INTERNATIONAL APPLICATION THAT WAS FILED WITH THE CHINESE PATENT OFFICE AS RECEIVING OFFICE

国际申请号:

PCT/CN03/00048

INTERNATIONAL APPLICATION NUMBER

国际申请日:

20 JAN 2003 (20. 01. 2003)

INTERNATILNAL FILING DATE

发明名称:

System and Method for Manufacture of a Hard Disc

TITLE OF INVENTION

Drive Arm and Bonding of Magnetic Head to

Suspension on a Drive Arm

申 请 人:

SAE MAGNETICS(H.K.)LTD

APPLICANT

中华人民共和国国家知识产权局局长
COMMISSIONER OF THE STATE INTELLECTUAL PROPERTY
OFFECE OF THE PEOPLE'S REPUBLIC OF CHINA

主意川

二零零三年二月二十八日 FEBRUARY. 28. 2003



PCT

REQUEST

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.

For re	ceiving	Office u	se only			
International Application	PCI	C/CN	03/ 0	0 (4	8
International Filing Date	20	JAN	2003	(2 (0. 0	1.0
FIO/CN Name of receiving Office	L FCT	人民共	和国国家	家知识 Applic	ation'	3 i

	Applicant's or agent's	file reference		
	(if desired) (12 characte	ers maximum) FPEL02150043		
Box No. 1 TITLE OF INVENTION System and Method for Manufacture of a Hard I	Disc Drive Arm and	d Bonding of Magnetic Head to		
Suspension on a Drive Arm				
Box No. 11 APPLICANT This person	n is also inventor			
Name and address: (Family name followed by given name: for a legal ent The address must include postal code and name of country. The country of t. Box is the applicant's State (that is, country) of residence if no State of residen	he address indicated in this	Telephone No.		
SAE MAGNETICS (H. K.) LTD.		Facsimile No.		
SAE Tower, 38-42 Kwai Fung Crescent		Teleprinter No.		
Kwai Chung N. T.				
Hong Kong Special Administrative Region,		Applicant's registration No. with the Office		
P. R. of China State (that is, country) of nationality:	State (that is, country)	of residence:		
CN	CN			
This person is applicant for the purposes of:		the United States the States indicated in of America only the Supplemental Box		
Box No. III FURTHER APPLICANT(S) AND/OR (FURT	HER) INVENTOR(S)			
Name and address: (Family name followed by given name: for a legal ent The address must include postal code and name of country. The country of I Box is the applicant's State (that is, country) of residence if no State of residen YAO, Minggao Winnerway Industrial Area, Nancheng, Dongguan City Guangdong Province, P. R. of China Zip Code: 511700	he address indicated in this ce is indicated helow.)	This person is: applicant only applicant and inventor inventor only (If this check-hox is marked, do not fill in below.) Applicant's registration No. with the Office		
State (that is, country) of nationality:	State (that is, country)	of residence:		
This person is applicant all designated all designate for the purposes of:	d States except tates of America	the United States of America only the Supplemental Box		
Further applicants and/or (further) inventors are indicated	on a continuation sheet.			
Box No. IV AGENT OR COMMON REPRESENTATIVE; OR ADDRESS FOR CORRESPONDENCE				
The person identified below is hereby/has been appointed to act of the applicant(s) before the competent International Authorities		agent common representative		
Name and address: (Family name followed by given name; for a legal ent The address must include postal code and name of c		Telephone No. (852)28284688		
CHINA PATENT AGENT (H.K.) LTD. 22/F, Great Eagle Centre	Facsimile No. (852)28271018			
23 Harbour Road, Wanchai Hong Kong Special Administrative Region		Teleprinter No.		
The People's Republic of China		Agent's registration No. with the Office		
Address for correspondence: Mark this check-box where space above is used instead to indicate a special address to	no agent or common rewhich correspondence	presentative is/has been appointed and the should be sent.		



Sheet No. 2....

Continuation of Box No. III FURTHER APPLICANT(S) A If none of the following sub-boxes is used, this sheet should not		•
Name and address: (Family name followed by given name; for a legal enting. The address must include postal code and name of country. The country of the Box is the applicant's State (that is, country) of residence if no State of residence SHIRAISHI, Masashi Flat C, 22/F, Tower 9 Laguna Varde (Phase IIA) Hung Hom, Kowloon	address indicated in this	This person is: applicant only applicant and inventor inventor only (If this check-hox is marked, do not fill in below.)
Hong Kong Special Administrative Region P. R. of China		Applicant's registration No. with the Office
State (that is, country) of nationality:	State (that is, country,) of residence:
This person is applicant all designated all designated for the purposes of:		the United States of America only the States indicated in the Supplemental Box
Name and address: (Family name followed by given name: for a legal enting The address must include postal code and name of country. The country of the Box to the applicant's State (that is, country) of residence if no State of residence XIE, Yiru Winnerway Industrial Area, Nancheng, Dongguan City Guangdong Province, P. R. of China Zip Code: 511700	address indicated in this	This person is: applicant only applicant and inventor inventor only (If this check-box is marked, do not fill in below.) Applicant's registration No. with the Office
State (that is, country) of nationality:	State (that is, country)) of residence:
This person is applicant all designated all designated for the purposes of:		the United States the States indicated in the Supplemental Box
Name and address: (Family name followed by given name; for a legal enting. The address must include postal code and name of country. The country of the Box is the applicant's State (that is, country) of residence if no State of residence	address indicated in this	This person is: applicant only applicant and inventor inventor only (If this check-hox is marked, do not fill in below.) Applicant's registration No. with the Office
State (that is, country) of nationality:	State (that is, country)	of residence:
This person is applicant all designated for the purposes of:		the United States the States indicated in the Supplemental Box
Name and address: (Family name followed by given name; for a legal enting. The address must include postal code and name of country. The country of the Box is the applicant's State (that is, country) of residence if no State of residence.	e address indicated in this	This person is: applicant only applicant and inventor inventor only (If this check-hox is marked, do not fill in helow.) Applicant's registration No. with the Office
State (that is, country) of nationality:	State (that is, country)	of residence:
This person is applicant all designated all designated for the purposes of:		the United States of America only the States indicated in the Supplemental Box
Further applicants and/or (further) inventors are indicated or	n another continuation	sheet.

Form PCT/RO/101 (continuation sheet) (March 2001; reprint July 2002)

See Notes to the request form



Sheet No. ...3.

				Sheet NoS			
Box No.	V DESIGNATION OF STATES	s ·	M	Mark the applicable check-hoxes below	; at	leas	t one must be marked.
The follo	owing designations are hereby made	und	er R	ule 4.9(a):			
Regiona	al Patent						
		M C	20001	bia, KE Kenya, LS Lesotho, MW	/ N.	1011	i M7 Mazambiana SD Sudan
□ Ar	SI Ciama Loana S7 Swariland T	7 1 1-	ii.ad	Republic of Tanzania, UG Uganda,	734	7	this 71 7 7 7 1 1 1 1 2 1 1 1 2 1 1 1 2 1 1 1 2 1
				Harare Protocol and of the PCT (if o			
_				• • • • • • • • • • • • • • • • • • • •			
□ EA				aijan, BY Belarus, KG Kyrgyzstan,			
		tan,	TM	Turkmenistan, and any other State v	vhic	h is	a Contracting State of the Eurasian
	Patent Convention and of the PCT						
□ EP	European Patent: AT Austria, BE	Bel	lgiur	n, BG Bulgaria, CH & LI Switzerlan	d an	d Li	echtenstein, CY Cyprus, CZ Czech
				Estonia, ES Spain, FI Finland, FR			
				Aonaco, NL Netherlands, PT Portugal			
				e of the European Patent Convention			
□ OA		_		n, CF Central African Republic, CG			
LI OA	C. Caban C. Cuinas CO Fare	DJ E	ociiii	uinea, GW Guinea-Bissau, ML Mal		ngo,	Cr Cole d Ivone, CW Cameroon,
				nich is a member State of OAPI and a dotted line)			
	of protection of treatment desired, s	peci	jy oi	doned ine)	• • •	• • •	
Nationa	I Patent (if other kind of protection	or a	treat	ment desired, specify on dotted line):			
□ AE I	United Arab Emirates		GM	Gambia		NZ.	New Zealand
	Antique and Rarbuda	$\overline{\Box}$	HD	Creatia			
	Alleria	\exists	1111	Croatia	Η	DII	DE III - I - I - I
	Albania	Η	HU				
	Armenia						Poland
				Israel			
				India			
\square AZ A	Azerbaijan		is	Iceland		RU	Russian Federation
☐ BA E	Bosnia and Herzegovina		JP	Japan			
□вв	Barbados		KE	Kenya		SD	Sudan
□ BG F	Bulgaria		KG	Kyrgyzstan		SE	Sweden
□ BR B	Brazil		KP	Democratic People's Republic		SG	Singapore
	Belarus			of Korea			
				Republic of Korea			
☐ CA (Sierra Leone
	& LI Switzerland and Liechtenstein						Tajikistan
	China				_		*
_	Zolombia			Liberia Liberia			Turkmenistan
		H	LK	Liberia			Tunisia
							Turkey
	Cuba				Ш	TT	Trinidad and Tobago
	Czech Republic				_		• • • • • • • • • • • • • • • • • • • •
	Germany		LV	Latvia	Ш	TZ	United Republic of Tanzania
	Denmark			Morocco			
	Dominica		MD	Republic of Moldova		UG	Uganda
\Box DZ A	Algería					US	United States of America
☐ EC I	Ecuador		MG	Madagascar			
EE I	Estonia		MK	The former Yugoslav Republic of		UZ	Uzbekistan
□ ES S	Spain			Macedonia		VN	Viet Nam
	Finland		MN	Mongolia			Yugoslavia
	United Kingdom			VMalawi	$\overline{\Box}$		South Africa
GD		_		Mexico			
	Georgia			Mozambique			
_	-				ш	ZW	Zimbabwe
□ GH (Ghana	Ш	NO	norway			
Check-be	oxes below reserved for designating	Stat	es u	which have become party to the PCT	after	. ice,	sance of this sheet:
				have become party to the FCT			
		_					
Precauti other des	ionary Designation Statement: In signations which would be permitte	add d un	litior der	n to the designations made above, the the PCT except any designation(s) i	ap ndic	plica ated	nt also makes under Rule 4.9(b) all in the Supplemental Box as being

other designations which would be permitted under the PCT except any designation(s) indicated in the Supplemental Box as being excluded from the scope of this statement. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit. (Confirmation (including fees) must reach the receiving Office within the 15-month time limit.)



Sheet No. ...4..

Box No. VI PRIORITY CLAIM				
The priority of the follo	wing earlier application(s) is here	by claimed:	•	
Filing date	Number of earlier application	V	Vhere earlier application	is:
of earlier application (day/month/year)	or earner application	national application: country or Member of WTO	regional application:* regional Office	international application: receiving Office
item (1)	·			. .
item (2)				
item (3)		_		
item (4) .	*	1		
				`
item (5)				
Further priority ela	nims are indicated in the Suppleme	ental Box.		
The receiving Office is if the earlier application above as:	requested to prepare and transmit was filed with the Office which for	to the International Bureau the purposes of this interna-	a a certified copy of the entional application is the r	earlier application(s) (only receiving Office) identified
	tem (1) item (2)	item (3) item	(4) item (5)	other, see Supplemental Box
	lication is an ARIPO application, i ne Memher of the World Trade O			
D. N. MIL INTER	NATIONAL CRAPCHING AL	THORITY		
Box No. VII INTER	NATIONAL SEARCHING AU			
Choice of Internation international search, inc	al Searching Authority (ISA) (if a dicate the Authority chosen; the two	two or more International S o-letter code may be used):	Searching Authorities are	competent to carry out the
ISA /				
Request to use results International Searching	of earlier search; reference to (Authority):	that search <i>(if an earlier so</i>	earch has been carried or	ut by or requested from the
Date (day/month/year)	Num	ber Cour	ntry (or regional Office)	
Box No. VIII DECLARATIONS				
The following declarations are contained in Boxes Nos. VIII (i) to (v) (mark the applicable Number of check-boxes below and indicate in the right column the number of each type of declaration): Number of declarations				
Box No. VIII (i)	Declaration as to the identi	ity of the inventor		:
Box No. VIII (ii)	Declaration as to the appli date, to apply for and be g	icant's entitlement, as at th granted a patent	e international filing	:
Box No. VIII (iii	•	licant's entitlement, as at to of the earlier application	_	· · · · · · · · · · · · · · · · · · ·
Box No. VIII (iv) Declaration of inventorsh United States of America	ip (only for the purposes o)	f the designation of the	÷
Box No. VIII (v) Declaration as to non-prej	judicial disclosures or exce	eptions to lack of novelty	<i>i</i> :

			í
heet	Nο		۰

Box No. IX CHECK LIST; LANGUAGE	OF FILING			
This international application contains: (a) the following number of sheets in paper form:	This international application is accompanied by the following item(s) (mark the applicable check-boxes below and indicate in right column the number of each item):	Number of items		
request (including	1. 🔀 fee calculation sheet	: 1		
declaration sheets) : 5	2. 🔀 original separate power of attorney	: 1		
description (excluding sequence listing part) : 5	3. original general power of attorney	: •		
claims : 4	4. copy of general power of attorney; reference number,			
abstract : 1	if any:			
drawings : 8	5. statement explaining lack of signature	:		
Sub-total number of sheets: 23	6. priority document(s) identified in Box No. VI as item(s):	:		
sequence listing part of description (actual number of sheets if filed in paper	7. translation of international application into (language):			
form, whether or not also filed in computer readable	8. separate indications concerning deposited microorgan or other biological material	ism :		
form; see (h) below) : Total number of sheets : 23	9. sequence listing in computer readable form (indicate all and number of carriers (diskette, CD-ROM, CD-R or o	so type . ther))		
(b) sequence listing part of description filed in computer readable form	(i) copy submitted for the purposes of international under Rule 13ter only (and not as part of the			
(i) only (under Section 801(a)(i))	international application)	dialog:		
(ii) in addition to being filed in paper form (under Section 801(a)(ii))	(ii) (only where check-hox (b)(i) or (b)(ii) is marke column) additional copies including, where app the copy for the purposes of international searce	licable,		
Type and number of carriers (diskette, CD-ROM, CD-R or other) on which the	Rule 13ter	:		
sequence listing part is contained (additional	(iii) together with relevant statement as to the ident of the copy or copies with the sequence listing			
copies to he indicated under item 9(ii), in right column):	mentioned in left column	:		
	10. dther (specify):	:		
Figure of the drawings which should accompany the abstract: Fig 3a	Language of filing of the international application:			
Box No. X SIGNATURE OF APPLICAN	T, AGENT OR COMMON REPRESENTATIVE			
	gning and the capacity in which the person signs (if such capacity is not obvious	from reading the request).		
(中)				
	For receiving Office use only			
Date of actual receipt of the purported international application:	2 0 JAN 2883 (2 0. 0 1. 0 3)	2. Drawings:		
Corrected date of actual receipt due to later timely received papers or drawings complet the purported international application:		received:		
4. Date of timely receipt of the required corrections under PCT Article 11(2):		not received:		
5. International Searching Authority (if two or more are competent): ISA /	6. Transmittal of search copy delayed until search fee is paid			
For International Bureau use only				
	For International Bureau use only			
Date of receipt of the record copy by the International Bureau:	For International Bureau use only			

This sheet is not part of and does not count as a sheet of the international application.

PCI

FEE CALCULATION SHEET Annex to the Request

For receiving Office use only

International Application No. PCT/CN 03/ 0 00 48

20 JAN 2003 (20.01.03) Applicant's or agent's FPEL02150043 file reference Date stamp of the receiving Office Applicant SAE MAGNETICS (H.K.) LTD. CALCULATION OF PRESCRIBED FEES CNY500 Τ 1. TRANSMITTAL FEE CNY1500 S SEARCH FEE . International search to be carried out by (If two or more International Searching Authorities are competent to carry out the international search, indicate the name of the Authority which is chosen to carry out the international search.) 3. INTERNATIONAL FEE Basic Fee Where item (b) of Box No. IX applies, enter Sub-total number of sheets 23 Where item (b) of Box No. IX does not apply, enter Total number of sheets CHT 650,-CHF650 first 30 sheets . . **b**2 number of sheets fee per sheet in excess of 30 additional component (only if sequence listing part of description is filed in computer readable form under Section 801(a)(i), or both in that form and on paper, under Section 801(a)(ii)): ь3 400 x fee per sheet В CHF650 Add amounts entered at b1, b2 and b3 and enter total at B. **Designation Fees** The international application contains designations. D amount of designation fee number of designation fees payable (maximum 5) **CHF790** I Add amounts entered at B and D and enter total at I . . . (Applicants from certain States are entitled to a reduction of 75% of the international fee. Where the applicant is (or all applicants are) so entitled, the total to be entered at I is 25% of the sum of the amounts entered at B and D.) P 4. FEE FOR PRIORITY DOCUMENT (if applicable) CNY2000CHF790 5. TOTAL FEES PAYABLE. TOTAL Add amounts entered at T, S, I and P, and enter total in the TOTAL box The designation fees are not paid at this time. MODE OF PAYMENT authorization to charge deposit account (see below) X postal money order ash cash coupons __ cheque bank draft revenue stamps other (specify): AUTHORIZATION TO CHARGE (OR CREDIT) DEPOSIT ACCOUNT Receiving Office: RO/_CN (This mode of payment may not be available at all receiving Offices) Deposit Account N Authorization to charge the total fees indicated above. Date: (This check-box may be marked only if the conditions for deposit accounts of the receiving Office so permit) Authorization to charge any deficiency Name: or credit any overpayment in the total fees indicated above. Authorization to charge the fee for priority document. Signature: he fee calculation sheet Form PCT/RO/101 (Annex) (January 2002; reprint July 2002)

10

15

20

25

SYSTEM AND METHOD FOR MANUFACTURE OF A HARD DISK DRIVE ARM AND BONDING OF MAGNETIC HEAD TO SUSPENSION ON A DRIVE ARM

5 Background Information

The present invention relates to magnetic hard disk drives. More specifically, the invention relates to a system for manufacturing a hard disk drive arm and the bonding of magnetic head to suspension on the drive arm.

Among the better known data storage devices are magnetic disk drives of the type in which a magnetic head slider assembly floats on an air bearing at the surface of a rotating magnetic disk. Such disk drives are often called 'Winchester'-type drives. In these, one or more rigid magnetic disks are located within a sealed chamber together with one or more magnetic head slider assemblies. The magnetic disk drive may include one or more rigid magnetic disks, and the slider assemblies may be positioned at one or both sides of the magnetic disks.

Figure 1 provides an illustration of a typical hard drive as used in the art. The slider assembly 108 may be mounted in a manner which permits gimbaled movement at the free outer end of the arm 102 such that an air bearing between the slider assembly 108 and the surface of the magnetic disk 104 can be established and maintained. The drive arm 102 is coupled to an appropriate mechanism, such as a voice-coil motor (VCM) 106, for moving the arm 102 across the surface of the disk 104 so that a magnetic head contained within the slider assembly 108 can address specific concentric data tracks on the disk 104 for writing information onto or reading information from the data tracks.

Figure 2 provides an illustration of a hard drive arm and magnetic head as used in the art. Typically, the magnetic head (slider) 202 is electrically connected to the head gimbal assembly (HGA) by bonding means, such as gold ball bonding (GBB), solder bump bonding (SBB), and ultrasonic welding. Typically, four

connection points (balls) 204 are provided to electrically connect the magnetic head 202 to the suspension tongue/head gimbal assembly (HGA) 206. Two of the balls 204 are for the 'read' operation, and two of the balls 204 are for the 'write' operation. To prevent the bonding balls 204 from hardening with the magnetic head 202 in an undesirable orientation, a fixture 208 is used to strongly clamp the suspension tongue 206 and head 202 to be physically stable for ball 204 application by a soldering tool 210, etc. A base support 211 and a first clamping cover 220 stabilize the magnetic head 202. A second clamping cover 221 stabilizes the suspension tongue 206. A second base support (not shown) secures the load beam 212. This fixture 208 is utilized to prevent a change in orientation of the head 202 by the force of the soldering tool 210 during application. However, the clamping force of the fixture 208 is often enough to deform the magnetic head 202 and suspension tongue 212 structure causing improper orientation(alignment). Further, the forces involved have a tendency to damage the head 202 surface as well as the head suspension dimple 214.

10

15

It is therefore desirable to have a system to enable magnetic head electrical bonding while avoiding the aforementioned problems, in addition to providing other advantages.

In an aspect of the present invention, a system for manufacturing a data storage device comprising: a placement device to physically stabilize a hard drive head device for electrical bonding of said head device to a hard drive arm component, wherein said placement device utilizes sub-ambient pressure to maintain the position of said head device with respect to said arm component for said electrical bonding.

In a further aspect of the present invention, a method for manufacturing a data storage device comprising:

physically stabilizing, by a placement device, a hard drive head device for electrical bonding of said head device to a hard drive arm component and utilizing, by said placement device, sub-ambient pressure to maintain the

position of said head device with respect to said arm component for said electrical bonding.

Brief Description Of The Drawings

- Figure 1 provides an illustration of a typical hard drive as used in the art.
 - Figure 2 provides an illustration of a hard drive arm and magnetic head as used in the art.
 - Figure 3 illustrates a hard drive arm suspension, magnetic head, and head placement device according to an embodiment of the present invention.
- Figure 4 illustrates placement device design according to two different embodiments of the present invention.
 - Figure 5 illustrates placement device design according to three additional embodiments of the present invention.
 - Figure 6 illustrates placement device design according to three further embodiments of the present invention.
 - Figure 7 illustrates placement device design for 'U'-shaped micro-actuator accommodation according to an embodiment of the present invention.
 - Figure 8 illustrates the design of a simultaneous operation placement device according to an embodiment of the present invention.

Detailed Description

20

Figure 3 illustrates a hard drive arm suspension, magnetic head, and head placement device according to an embodiment of the present invention. As shown in figure 3a, in one embodiment, the placement device 305 has two vacuum tubes 301,304. The first vacuum pipe (tube) 301 has a fixture 311 that mates to the magnetic head 321 of a hard drive. As shown in figure 3b, in this embodiment, the first vacuum tube fixture 311 has a stepped 313 surface that mates with the head 321 in such a way that prevents rotational motion of the head 321 with respect to the placement device 305 (and thus, the suspension tongue 322). In one

embodiment, the step 313 is between 100 micrometers and 280 micrometers. In one embodiment, the second vacuum tube has a fixture mate-able to the load beam 324. Further, an alignment pin 303 is provided that is capable of being inserted into the tooling hole of the load beam 324 for ensuring proper alignment. In this embodiment, the placement device is secured to the magnetic head 321 and load beam 324 by sub-ambient pressure imposed by the first 301 and second 302 vacuum tubes, the first vacuum tube 301 applying suction force to the air bearing surface (ABS) of the slider/head 321 and the second vacuum tube 302 applying suction force to the load beam 324.

Figure 4 illustrates placement device design according to two different embodiments of the present invention. In one embodiment, shown in figure 4a and 4b, the fixture 402 of the first vacuum tube has an integrated step 403 to prevent rotational (yaw) 406 and longitudinal 408 motion of the magnetic head 404 during bonding ball 410 application. In another embodiment, shown in figure 4c and 4d, the fixture 412 of the first vacuum tube has an externally-mounted step structure 413. Further, figures 4b and 4d illustrate the air inlets of the first and second vacuum tubes.

Figure 5 illustrates placement device design according to three additional embodiments of the present invention. As shown in figure 5b, in one embodiment, an externally-mounted step structure 501 is provided with a side protrusion 502 to prevent transverse 503 motion (as well as longitudinal 504 and rotational 505 motion) of the magnetic head 508 (See figure 5a). As shown in figure 5c, in another embodiment, an externally-mounted step structure 511 is provided with two side protrusions 512 to prevent transverse 513 motion (as well as longitudinal 514 and rotational 515 motion) of the magnetic head 508 (See figure 5a). As shown in figure 5d, in yet another embodiment, an externally-mounted step structure 521 is provided with two side protrusions 522. Further, in this embodiment, a notch 524 is provided in the step 521 to allow for arm component clearance.

Figure 6 illustrates placement device design according to three further embodiments of the present invention. As shown in figure 6b, in one embodiment, the first vacuum tube 602 has an 'L'-shaped step structure 601 integrated in its mating surface to prevent transverse 603 motion (as well as longitudinal 604 and rotational 605 motion) of the magnetic head 608 (See figure 6a). As shown in figure 6c, in another embodiment, the first vacuum tube 612 has a 'U'-shaped step structure 611 integrated in its mating surface. As shown in figure 6d, in yet another embodiment, the first vacuum tube 622 has a 'U'-shaped step structure 621 integrated in its mating surface with a notch 623 provided to allow for arm component clearance.

10

15

20

25

Figure 7 illustrates placement device design for 'U'-shaped micro-actuator accommodation according to an embodiment of the present invention. As shown in figures 7b, 7c, and 7d, in one embodiment, a first vacuum tube 702 has an externally-mounted step 704 and two side-mounted steps 706 to restrict the motion of a magnetic head 708 that is mounted in a micro-actuator, such as a 'U'-shaped micro-actuator 710. This embodiment accommodates the shape of such a micro-actuator 710 while preventing the motion of the head 708 and micro-actuator 710 during the bonding process.

Figure 8 illustrates the design of a simultaneous operation placement device according to an embodiment of the present invention. In one embodiment, multiple individual placement devices 802 are combined into one machine 804 in order to stabilize components of many hard drive load arms for simultaneous head bonding operations.

Although several embodiments are specifically illustrated and described herein, it will be appreciated that modifications and variations of the present invention are covered by the above teachings and within the purview of the appended claims without departing from the spirit and intended scope of the invention.

20

What is claimed is

- 1.A system for manufacturing a data storage device comprising:
 a placement device to physically stabilize a hard drive head device for electrical bonding of said head device to a hard drive arm component, wherein said placement device utilizes sub-ambient pressure to maintain the position of said head device with respect to said arm component for said electrical bonding.
- 2. The system of claim 1, wherein said hard drive head device is a hard disk drive magnetic head.
 - 3. The system of claim 2, wherein said hard drive arm component is a suspension tongue.
- 15 4. The system of claim 1, wherein said electrical bonding is ball bonding.
 - 5. The system of claim 4, kwherein said electrical bonding is a type selected from the group consisting of gold ball bonding (GBB), solder bump bonding (SBB), ultrasonic welding, and stitch bonding.
 - 6. The system of claim 1, wherein said placement device includes a first vacuum tube structure for providing said sub-ambient pressure to affix said first vacuum tube structure to said head device.
- 7. The system of claim 6, further comprising an alignment pin protruding from said placement device.
 - 8. The system of claim 7, wherein said alignment pin is capable of being inserted into a suspension tooling hole for ensuring said proper alignment.

9. The system of claim 7, further comprising a second vacuum tube structure for providing sub-ambient pressure, wherein said first vacuum tube structure vacuum-couples to said head device and said second vacuum tube structure vacuum-couples to a suspension load beam attached to said arm component.

5

15

- 10. The system of claim 9, wherein the first vacuum tube structure includes a step structure mate-able to an edge of the head device.
- 10 11. The system of claim 10, wherein said step structure is mate-able to one or more edges of said head device.
 - 12. The system of claim 11, wherein said step structure is an integral structure of the first vacuum tube.
 - 13. The system of claim 11, wherein said step structure is an external structure.
- 14. The system of claim 9, wherein said first vacuum tube structure is a material selected from the group consisting of Stainless Steel, Copper, Aluminum Oxide, Polyimide, and Ceramic.
 - 15. The system of claim 9, wherein said second vacuum tube structure is a material selected from the group consisting of Stainless Steel, Copper, Aluminum Oxide, Polyimide, and Ceramic.
 - 16.A method for manufacturing a data storage device comprising: physically stabilizing, by a placement device, a hard drive head device for electrical bonding of said head device to a hard drive arm component and utilizing, by said placement device, sub-ambient pressure to maintain the

position of said head device with respect to said arm component for said electrical bonding.

- 17. The method of claim 16, wherein said hard drive head device is a hard disk drive magnetic head.
 - 18. The method of claim 17, wherein said hard drive arm component is a suspension tongue.
- 19. The method of claim 16, wherein said electrical bonding is ball bonding.
 - 20. The method of claim 19, wherein said electrical bonding is a type selected from the group consisting of gold ball bonding (GBB), solder bump bonding (SBB), ultrasonic welding, and stitch bonding.
 - 21. The method of claim 16, wherein said placement device includes a first vacuum tube structure for providing said sub-ambient pressure to affix said first vacuum tube structure to said head device.
- 22. The method of claim 21, further comprising: providing an alignment pin protruding from said placement device.

15

- 23. The method of claim 22, wherein said alignment pin is capable of being inserted into a suspension tooling hole for ensuring said proper alignment.
- 24. The method of claim 22, further comprising:
 providing sub-ambient pressure, by a second vacuum tube;
 vacuum-coupling said first vacuum tube structure to said head device; and
 vacuum-coupling said second vacuum tube structure to a suspension load beam

- 25. The method of claim 24, wherein the first vacuum tube structure includes a step structure mate-able to an edge of the head device.
- 26. The method of claim 25, wherein said step structure is mate-able to at least the leading edge of said head device.
- 27. The method of claim 24, wherein said first vacuum tube structure is a material selected from the group consisting of Stainless Steel, Copper, Aluminum Oxide, Polyimide, and Ceramic.
 - 28. The method of claim 24, wherein said second vacuum tube structure is a material selected from the group consisting of Stainless Steel, Copper, Aluminum Oxide, Polyimide, and Ceramic.



Abstract

A system and method are disclosed for the manufacture of a hard disk drive arm and the bonding of magnetic head to suspension on the drive arm.








FIG.1 (Prior Art)









F 16.3





F1G. 5

F16. 5d



16.6

